

LOAD : DISTANCE LIFT LIMITS. KGS

BOOM ANGLE	LOAD RADIUS IS MEASURED FROM CENTRE LINE OF SLEW					
	NON TRAVEL S.W.L. BOOM MIN. EXTENSION	TRAVEL S.W.L. BOOM MIN. EXTENSION	LOAD RADIUS METRES	NON TRAVEL S.W.L. BOOM MAX. EXTENSION	TRAVEL S.W.L. BOOM MAX. EXTENSION	LOAD RADIUS METRES
58°	2200	1000	1.07	1000	500	2.30
50°	1730	1000	1.35	830	415	2.90
40°	1295	777	1.80	630	315	3.65
30°	1040	624	2.25	510	255	4.30
20°	880	528	2.60	395	197	4.75
10°	750	450	2.99	362	181	5.10
0°	710	426	3.00	360	180	5.11

CX220 2.2 TONNE CAPACITY

**NB: LOAD RADIUS IS MEASURED FROM THE
CENTRE LINE OF THE SLEW RING**

- A) ONLY TRAVEL WITH SUSPENDED LOAD
WHEN ON FIRM AND LEVEL GROUND.
- B) EXAGGERATED WEAR OR DAMAGE CAUSED
BY USE IN TRAVELING MODE WITH LOAD
SUSPENDED IS NOT COVERED BY WARRANTY.